

1. High Efficiency ; Long Life ; Outstanding Reliability .
2. Provided Class Leading Performance .
3. Offered Different Fixed Beam Angles 10 , 30 , 60 Degrees , Suitable for any Environment's application.
4. Ultra Low Maintenance .
5. Built-in Blower.
6. The IRL series offered AC24V & DC12V .
7. Super Leading class PSU Built-in ; Start working temperature from **- 40°C to 60°C** . It can suit any environments .
8. Outstanding Night time images .
9. Even output Illumination ; Zero light pollution .



Specifications :

Model No:	IRL1	IRL2
IR Range	150M-200M (492ft - 656ft)	
IR LED	24 Pcs of High output LEDs	
IR WaveLength	850nm	
IR Life Time	20000 Hour	
IR Radiation Angle	10 Degrees	
IR Control	Auto Photo Cell Sensor	
Ambient	- 20 ~ 50°C ; 30 ~ 90% RH	
Dimensions	135(W) x158(H) X 180(D)mm	
Weights	Approx.1.8KGS	Approx.1.9KGS
Power Source	DC12V	AC24V
Power Consumption	13W	16.3W
IR Sensitivity	Variable Through VR (Slect a timing to turn on or off or Variable VR Depending On The Lens Iris Dark or Bright	
Front & Rear cover of housing	High Impact Poly Carbonate	
Housing and Sunshield	Aluminum Alloy	
Weather-proof	YES	